

## imageCLASS MF269dw/MF267dw MF264dw

# imageCLASS MF269dw/MF267dw/MF264dw

Black and White | Compact | Multifunction

Print up to 30 ppm

Print up to 8-1/2" x 14"

250-sheet maximum paper capacity

Standard one-year warranty

Designed for small and home offices, the imageCLASS MF269dw/MF267dw/MF264dw models balance speedy performance and minimal maintenance, and the LCD panel delivers an intuitive user experience.





#### USABILITY

- Six-line touch LCD for easy navigation (MF269dw/MF267dw only).
- Create Wi-Fi<sup>®</sup> Direct hotspot from the printer to establish direct connection to mobile device(s) without the need for an external router.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low-energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR<sup>®</sup> certified and currently rated EPEAT<sup>®</sup> Silver.<sup>1</sup>



#### QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and help minimize the impact on support resources.
- Canon GENUINE supplies help ensure enhanced quality, performance, and life cycle of your Canon equipment.



## **COST EFFICIENCY**

- Out-of-the-box, standard two-sided printing plus the ability to print multiple pages onto one page helps to reduce paper consumption.
- Available high-capacity cartridge helps reduce overall supply costs.



## WORKFLOW EFFICIENCY

- Supports mobile solutions<sup>3</sup> for printing and scanning.
- Scan and convert documents to searchable digital files.
- Designed for smaller print jobs with first-print time as fast as 5.1 seconds.



## SECURITY FEATURES

- Helps mitigate risk of confidential information loss, as documents are only stored in short-term memory.
- Security settings can be set behind an administrator log-in.



## MOBILE-FRIENDLY DEVICE ACCESS

From application-based to cloud-based to device native, the imageCLASS MF269dw/MF267dw/MF264dw models offer a variety of methods for printing from a mobile phone or tablet across iOS and Android devices. The Canon PRINT Business application, which supports both platforms, offers access to additional device settings as well as the ability to scan from the printer to a mobile phone or tablet.



## EFFICIENT DOCUMENT SCANNING

The imageCLASS MF269dw/MF267dw/MF264dw leverage a document feeder for scanning, as well as the ability to convert files into multiple formats, including Hi-compression PDF and Searchable PDF (OCR). All three models offer the ability to do color scanning while the MF269dw offers two-sided scanning through the feeder.



#### 100% U.S.-BASED SERVICE AND SUPPORT

From cutting-edge technology to industry-leading response times, Canon U.S.A. takes pride in delivering complete customer satisfaction. Canon's award-winning, 100% U.S.based, friendly, and knowledgeable Customer Service team provides expert assistance for every level of experience, giving you the support, peace of mind, and value your business deserves.



#### **GENUINE® CONSUMABLES**

Always look for the Canon anti-counterfeiting hologram on your Canon GENUINE product packaging.

Use of Canon GENUINE toner cartridges helps provide longer equipment life, high yields, reliable performance, high-quality output, and minimal jamming or issues.

## SPECIFICATIONS

FEATURES	imageCLASS MF269dw	imageCLASS MF267dw	imageCLASS MF264dw
		MAIN UNIT	
Functions	Print/Scan/Co		Print/Scan/Copy
Control Panel	6-line LCD		5-line LCD
Memory	256 MB		
Standard Interface Connection	USB Device 2.0 High-Speed, 10/100 Base-T Ethernet (Network), Wi-Fi 802.11 b/g/n, Wi-Fi Direct Connection		
Paper Input/Output Capacity (Letter, 20 lb. Bond)	250/50 Sheets		
Paper Sources (Letter, 20 lb. Bond)	250-sheet Paper Cassette, 1-sheet Stack Bypass		
Supported Media Types	Cassette/Bypass: Plain, Recycled, Thick, Bond, Label, Envelope		
Supported Media Sizes	Cassette/Bypass: Letter, Legal, Statement, Executive; Envelope: COM10, Monarch, C5, DL; Custom (Min. 3" x 5" to Max. 8.5" x 14")		
Supported Media Weights			
Narm-up Time	Cassette/Bypass: 16 lb. Bond to 43 lb. Bond (60 to 163 g/m <sup>2</sup> )		
•	From Power On: 15 Seconds or Less; From Sleep Mode: 1.6 Seconds or Less		
Dimensions (W x D x H)		" x 16.0" x 14.8" (390 mm x 405 mm x 375 mm)	
Neight (Machine Only/Boxed Weight)	29.3 lb. (13.3 kg)/37.4 lb. (17.0 kg)	27.3 lb. (12.4 kg)/3	5.2 lb. (16.0 kg)
		PRINT SPECIFICATIONS	
Printing Method	Laser Beam Printing		
Print Speeds <sup>2</sup>	Up to 30 ppm (Letter); Up to 24 ppm (Legal)		
irst-Print-Out Time	Approx. 5.1 Seconds		
ecommended Monthly Page Volume	250 - 2,500 Pages		
Print Resolution (dpi)	600 x 600		
Standard Page Description Languages	UFR II-LT, PCL*6, PCL*5e		
wo-Sided Printing		Automatic (Standard)	
Printing from Mobile and Cloud-based Services <sup>3</sup>	Canon PRINT Business, Apple® AirPrint®, Mopria™ Print Service, Google Cloud Print™ <sup>4</sup>		
		s Server* 2016/2012 R2/2012/2008 R2/2008; Mac	
Operating Systems (Print/Scan)		able For Download From <b>www.usa.canon.com/suppo</b>	
	COPY SPECIFICATIONS		
Copy Speed	Up to 30 ppm (Letter); Up to 24 ppm (Legal)		
First-Copy-Out Time (Letter)	8 Seconds or Less		
Copy Resolution (dpi)	6 Seconds of Less Up to 600 x 600		
Copy Size			
Presets	Platen: Up to Letter; ADF: Up to Legal           Magnifications: 25% - 400% (1% Increments)/Reductions: 25%, 50%, 64%, 78%/Enlargements: 129%, 200%, 400%		
	Magnifications: 25% - 400% (1% Incr	SCAN SPECIFICATIONS	ments: 129%, 200%, 400%
	Dude in Alternatio Decement Freder		en el Escale e
lype	Duplexing Automatic Document Feeder	Automatic Docur	
Document Feeder Paper Capacity (20 lb. Bond)	50 Sheets 35 Sheets		
Document Feeder Supported Media Sizes		Legal, Letter	
Document Feeder Supported Media Weights	Single-sided Scanning: 13 - 28 lb. Bond (50-105 g/m <sup>2</sup> )	Single-sided Scanning: 13 - 2	8 lb. Bond (50-105 g/m²)
	Single-sided Scanning: 13 - 28 lb. Bond (50-105 g/m <sup>2</sup> ) Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m <sup>2</sup> )		8 lb. Bond (50-105 g/m²)
Document Feeder Supported Media Weights Scan Resolution (dpi)		600 × 600	8 lb. Bond (50-105 g/m²)
	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m <sup>2</sup> )	600 x 600 Canon PRINT Business	
Scan Resolution (dpi) Scan-to-Mobile Devices	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)	600 x 600 Canon PRINT Business Single-sided (Color	<b>r∕BW)</b> : 8 ∕10.6
ican Resolution (dpi) ican-to-Mobile Devices	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m <sup>2</sup> )	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color	<b>r∕BW):</b> 8 ∕10.6
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm)	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)         Single-sided (Color/BW): 7.7/11.6         Two-sided (Color/BW): 2.4/4	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS	<b>r∕BW):</b> 8 ∕10.6
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)         Single-sided (Color/BW): 7.7/11.6         Two-sided (Color/BW): 2.4/4         Email (SMTP), SMB,	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX	<b>r∕BW):</b> 8 ∕10.6
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)         Single-sided (Color/BW): 7.7/11.6         Two-sided (Color/BW): 2.4/4	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX	<b>r∕BW):</b> 8 ∕10.6
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination Address Book	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)         Single-sided (Color/BW): 7.7/11.6         Two-sided (Color/BW): 2.4/4         Email (SMTP), SMB,	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX	<b>r∕BW):</b> 8 ∕10.6
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi)	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)         Single-sided (Color/BW): 7.7/11.6         Two-sided (Color/BW): 2.4/4         Email (SMTP), SMB,         Local (50	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX ) 0	r/BW): 8/10.6 r/BW): N/A
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol	Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (51           300 x 30	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX ) 0 MTP, POP3	r/BW): 8/10.6 r/BW): N/A
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol	Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (51           300 x 30           File: SMB; Email: S	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX ) 0 MTP, POP3	r/BW): 8/10.6 r/BW): N/A
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol File Format	Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (51           300 x 30           File: SMB; Email: S	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX ) 0 MTP, POP3 act, Searchable) FAX SPECIFICATIONS	r/BW): 8/10.6 r/BW): N/A
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Sommunication Protocol File Format Modem Speed	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²) Single-sided (Color/BW): 7.7/11.6 Two-sided (Color/BW): 2.4/4 Email (SMTP), SMB, Local (50 300 x 30 File: SMB; Email: S TIFF, JPEG, PDF (Comp	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX ) 0 MTP, POP3 act, Searchable) FAX SPECIFICATIONS G3: 14.4 Kbps	r/BW): 8/10.6 r/BW): N/A
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination Address Book iend Resolution (dpi) icommunication Protocol iile Format Modem Speed Resolution (dpi)	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²) Single-sided (Color/BW): 7.7/11.6 Two-sided (Color/BW): 2.4/4 Email (SMTP), SMB, Local (50 300 x 30 File: SMB; Email: S TIFF, JPEG, PDF (Comp Super G3: 33.6 Kbps;	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX ) 0 MTP, POP3 act, Searchable) FAX SPECIFICATIONS G3: 14.4 Kbps 0, 200 x 100	r/BW): 8 /10.6 r/BW): N/A
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination Address Book iend Resolution (dpi) icommunication Protocol iile Format Modem Speed Resolution (dpi) iending/Recording Size	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)           Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (50           300 x 30           File: SMB; Email: S           TIFF, JPEG, PDF (Comp           Super G3: 33.6 Kbps;           200 x 400, 200 x 20           Statement to	600 x 600 Canon PRINT Business Single-sided (Color Two-sided (Color SEND SPECIFICATIONS Super G3 FAX ) 0 MTP, POP3 act, Searchable) FAX SPECIFICATIONS G3: 14.4 Kbps 0, 200 x 100 Letter	r/BW): 8 /10.6 r/BW): N/A
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination Address Book iend Resolution (dpi) iommunication Protocol iile Format Modem Speed tesolution (dpi) iending/Recording Size iax Memory	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)           Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (50           300 x 30           File: SMB; Email: S           TIFF, JPEG, PDF (Comp           Super G3: 33.6 Kbps;           200 x 400, 200 x 20           Statement to           Up to 256 F	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         SEND SPECIFICATIONS         Super G3 FAX         0)         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages	r/BW): 8 /10.6 r/BW): N/A
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination Address Book iend Resolution (dpi) communication Protocol ille Format Modem Speed Resolution (dpi) iending/Recording Size isax Memory ispeed Dials	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)           Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (50           300 x 30           File: SMB; Email: S           TIFF, JPEG, PDF (Comp           Super G3: 33.6 Kbps;           200 x 400, 200 x 20           Statement to           Up to 256 F           Max. 10	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         SEND SPECIFICATIONS         Super G3 FAX         0)         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         4	r/BW): 8/10.6 r/BW): N/A
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination Address Book iend Resolution (dpi) immunication Protocol ille Format Modem Speed Resolution (dpi) iending/Recording Size iax Memory ispeed Dials iroup Dials/Destinations	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)           Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (50           300 x 30           File: SMB; Email: S           TIFF, JPEG, PDF (Comp           Super G3: 33.6 Kbps;           200 x 400, 200 x 20           Statement to           Up to 256 F           Max. 10           Max. 50 D	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color SEND SPECIFICATIONS         Super G3 FAX         0)         00         MTP. POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         4         als	r/BW): 8/10.6 r/BW): N/A
ican Resolution (dpi) ican-to-Mobile Devices ican Speed (Letter) (ipm) Destination Address Book iend Resolution (dpi) immunication Protocol ille Format Modem Speed Resolution (dpi) isending/Recording Size irax Memory ispeed Dials iroup Dials/Destinations isequential Broadcast	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)           Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (50           300 x 30           File: SMB; Email: S           TIFF, JPEG, PDF (Comp           Super G3: 33.6 Kbps;           200 x 400, 200 x 20           Statement to           Up to 256 F           Max. 10           Max. 114 Add	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         SEND SPECIFICATIONS         Super G3 FAX         0)         00         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         4         als         esses	r/BW): 8/10.6 r/BW): N/A
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol File Format Modem Speed Resolution (dpi) Sending/Recording Size Fax Memory Speed Dials Group Dials/Destinations Sequential Broadcast	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)           Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (50           300 x 30           File: SMB; Email: S           TIFF, JPEG, PDF (Comp           Super G3: 33.6 Kbps;           200 x 400, 200 x 20           Statement to           Up to 256 F           Max. 10           Max. 50 D	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         SEND SPECIFICATIONS         Super G3 FAX         0)         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         4         als         esses         , Density, Sharpness, Duplex Fax	r/BW): 8/10.6 r/BW): N/A
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol File Format Modem Speed Resolution (dpi) Sending/Recording Size Fax Memory Speed Dials Group Dials/Destinations Sequential Broadcast Fax Features	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)           Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (51           300 x 30           File: SMB; Email: S           TIFF, JPEG, PDF (Comp           Super G3: 33.6 Kbps;           200 x 400, 200 x 20           Statement to           Up to 256 F           Max. 10           Max. 50 D           Max. 114 Add           Rx Mode, Resolution, Two-sided Origina	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         SEND SPECIFICATIONS         Super G3 FAX         0)         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         als         esses         , Density, Sharpness, Duplex Fax         SECUIRTY SPECIFICATIONS	r/BW): 8 /10.6 r/BW): N/A NA
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol File Format Modem Speed Resolution (dpi) Sending/Recording Size Fax Memory Speed Dials Group Dials/Destinations Sequential Broadcast Fax Features	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)           Single-sided (Color/BW): 7.7/11.6           Two-sided (Color/BW): 2.4/4           Email (SMTP), SMB,           Local (51           300 x 30           File: SMB; Email: S           TIFF, JPEG, PDF (Comp           Super G3: 33.6 Kbps;           200 x 400, 200 x 20           Statement to           Up to 256 F           Max. 10           Max. 50 D           Max. 114 Add           Rx Mode, Resolution, Two-sided Origina	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         SEND SPECIFICATIONS         Super G3 FAX         0)         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         4         als         esses         , Density, Sharpness, Duplex Fax	r/BW): 8/10.6 r/BW): N/A NA
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol File Format Modem Speed Resolution (dpi) Sending/Recording Size Fax Memory Speed Dials Sequential Broadcast Fax Features Network	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²) Single-sided (Color/BW): 7.7/11.6 Two-sided (Color/BW): 2.4/4 Email (SMTP), SMB, Local (51 300 x 30 File: SMB; Email: 5 TIFF, JPEG, PDF (Comp Super G3: 33.6 Kbps; 200 x 400, 200 x 20 Statement to Up to 256 F Max. 10 Max. 50 D Max. 114 Add Rx Mode, Resolution, Two-sided Origina IP/MAC Address Filtering, TLS Encrypted Communi	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         SEND SPECIFICATIONS         Super G3 FAX         0)         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         als         esses         , Density, Sharpness, Duplex Fax         SECUIRTY SPECIFICATIONS	r/BW): 8/10.6 r/BW): N/A NA
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol File Format Modem Speed Resolution (dpi) Sending/Recording Size Fax Memory Speed Dials Sequential Broadcast Fax Features Network	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²) Single-sided (Color/BW): 7.7/11.6 Two-sided (Color/BW): 2.4/4 Email (SMTP), SMB, Local (51 300 x 30 File: SMB; Email: 5 TIFF, JPEG, PDF (Comp Super G3: 33.6 Kbps; 200 x 400, 200 x 20 Statement to Up to 256 F Max. 10 Max. 50 D Max. 114 Add Rx Mode, Resolution, Two-sided Origina IP/MAC Address Filtering, TLS Encrypted Communi	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color SEND SPECIFICATIONS         Super G3 FAX         0)         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         als         esses         , Density, Sharpness, Duplex Fax         SECUIRTY SPECIFICATIONS         Sator, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authent	r/BW): 8/10.6 r/BW): N/A NA
Scan Resolution (dpi) Scan-to-Mobile Devices Scan Speed (Letter) (ipm) Destination Address Book Send Resolution (dpi) Communication Protocol File Format Modem Speed Resolution (dpi) Sending/Recording Size Fax Memory Speed Dials Group Dials/Destinations Sequential Broadcast Fax Features Network Wi-Fi° Authentication Methods	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)         Single-sided (Color/BW): 7.7/11.6         Two-sided (Color/BW): 2.4/4         Email (SMTP), SMB,         Local (50         300 x 30         File: SMB; Email: S         TIFF, JPEG, PDF (Comp         Super G3: 33.6 Kbps;         200 x 400, 200 x 20         Statement to         Up to 256 F         Max. 10         Max. 50 D         Max. 114 Add         Rx Mode, Resolution, Two-sided Origina         IP/MAC Address Filtering, TLS Encrypted Communi         WEP 6	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         SEND SPECIFICATIONS         Super G3 FAX         0         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         agges         als         esses         , Density, Sharpness, Duplex Fax         SECUIRTY SPECIFICATIONS         Eation, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authent         //128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)	r/BW): 8 / 10.6 r/BW): N/A NA NA
Scan Resolution (dpi)	Two-sided Scanning: 16 - 28 lb. Bond (60-105 g/m²)         Single-sided (Color/BW): 7.7/11.6         Two-sided (Color/BW): 2.4/4         Email (SMTP), SMB,         Local (50         300 x 30         File: SMB; Email: S         TIFF, JPEG, PDF (Comp         Super G3: 33.6 Kbps;         200 x 400, 200 x 20         Statement to         Up to 256 F         Max. 10         Max. 50 D         Max. 114 Add         Rx Mode, Resolution, Two-sided Origina         IP/MAC Address Filtering, TLS Encrypted Communi         WEP 6	600 x 600         Canon PRINT Business         Single-sided (Color Two-sided (Color         Send SPECIFICATIONS         Super G3 FAX         0)         0         MTP, POP3         act, Searchable)         FAX SPECIFICATIONS         G3: 14.4 Kbps         0, 200 x 100         Letter         ages         4         als         esses         , Density, Sharpness, Duplex Fax         SECUIRTY SPECIFICATIONS         sation, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authent         //128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)         ENVIRONMENTAL SPECIFICATIONS	r/BW): 8 / 10.6 r/BW): N/A NA NA

## **CONFIGURATION AND ACCESSORIES**



#### **Extended Service Plans Available For Purchase**

If service is required, you may receive a replacement model<sup>6</sup> via advanced exchange. In this case, you'll be instructed to return the damaged unit to Canon in the replacement packaging, which also includes a prepaid shipping label. Or you may choose to carry your existing equipment to a local Authorized service facility for repair.

#### Canon eCarePAK (Exchange/Carry-In)

Canon extended service plans extend standard, one-year warranty<sup>5</sup> support to cover an additional one to four years.

One-Year:	5707B042
Two-Year:	5707B043
Three-Year:	5707B044
Four-Year:	5707B045

#### **Item Codes**

imageCLASS MF269dw: 2925C006 imageCLASS MF267dw: 2925C010 imageCLASS MF264dw: 2925C020 Cartridge 051: 2168C001 (Yields 1,700 Pages) Cartridge 051 H: 2169C001 (Yields 4,100 Pages) Drum Cartridge 051: 2170C001 (Yields up to 23,000 Pages)

Standard Toner Cartridge 051 yielding 1,700 pages included with purchase.

<sup>1</sup> For current EPEAT ratings (Gold/Silver/Bronze), please visit **epeat.net**.

- <sup>2</sup> Print speed is based on internal testing. Print speed may vary, depending on the number of copies selected as well as the settings for size, type, and orientation of paper. <sup>3</sup> Canon PRINT Business is a free app available on the App Store\* and Google Play<sup>™</sup> Store. For more information, including compatibility, please visit **usa.canon.com/mobile-app**. Please see the respective websites for Apple AirPrint and Mopria Print Service for compatibility and additional information.
- <sup>4</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.
   <sup>5</sup> Warranty program is subject to certain conditions and restrictions. See warranty card for details.
   <sup>6</sup> Replacement model may be new or refurbished quality.



As an ENERGY STAR partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageCLASS, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of these features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2018 Canon U.S.A., Inc. All rights reserved.

0213W954 0818-iCMF269/267/264-PDF-IH



